



## Technical specifications Single Moulds

This single mould has 'protected-perforation'. The perforation is protected against damages and the special pattern also strengthens the construction. Beside that a sheet thickness of 15 mm is used. The perforation channels are rather short: only 3 mm. For cleaning purposes this is ideal, the chance of blocked perforation becomes negligible.

Ø PRESSED	APPROXIMATE WEIGHT
115x85	0,4 KG
142x101	1,5 KG
199x99	1,5 KG
220x100	2 KG
224x119	2 KG
237x115	2,5 KG
244x116	2,5 KG
240x120	2,5 KG
250x100	2,75 KG
206x101	2,2 KG
263x89	3 KG
279,5x96,8	3 KG
283x99	3 KG
282x98	3 KG
276x115	3 KG
290x105	3,5 KG
293x109	4 KG
296x148	4 KG
296x148	3,5 - 4 KG
300x100	3,5 - 4 KG
300x120	4 KG
325x117	4 KG
301x202	5 KG
343x303	9 KG
350x270	10 KG
362x287	11 KG
450x360	13 KG
370x240	9 KG
380x300	13 KG
424x100	5 KG
421x100	6 KG
439x99	4,5 KG
440x100	4,5 KG
431x271	12 KG
430x324	16 KG
428x280	15 KG
500x100	6 KG
500x200	11 KG
500x202	11 KG
498,5x298,5	15 KG
498,5x298,5	15 KG
618x103	7 KG

